

Revision: 24.01.2021

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Styrene
- CAS Number: 100-42-5
- **EC number:** 202-851-5
- Index number: 601-026-00-0
- · Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Shrne Chemicals
- · Further information obtainable from:



Product safety department. info@shrinechemicals.com

2 Hazards identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Acute Tox. 5 H303 May be harmful if swallowed.

- · Label elements
- · GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

May be harmful if swallowed.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 2)

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

(Contd. of page 1)

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Substances
- · CAS No. Description 100-42-5 styrene
- · Identification number(s) · EC number: 202-851-5
- · Index number: 601-026-00-0

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

ΑE

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

(Contd. of page 2)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

· Ingredients with limi	Ingredients with limit values that require monitoring at the workplace:		
100-42-5 styrene			
PEL (USA)	Long-term value: 100 ppm Ceiling limit: 200; 600* ppm *5-min peak in any 3 hrs		
REL (USA)	Short-term value: 425 mg/m³, 100 ppm Long-term value: 215 mg/m³, 50 ppm		
TLV (USA)	Short-term value: 20 ppm Long-term value: 10 ppm BEI, OTO		
WEL (Great Britain)	Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm		

(Contd. on page 4)

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

(Contd. of page 3)

· Ingredients with biological limit values:

100-42-5 styrene

BEI (USA) 400 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Mandelic acid plus phenylglyoxylic acid (nonspecific)

0.2 mg/L

Medium: venous blood Time: end of shift

Parameter: Styrene (semi-quantitative)

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

(Contd. on page 5)

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

	(Contd. of page
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	-30.7 °C v: 145.2 °C
· Flash point:	31 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	480 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits: Lower: Upper:	1.2 Vol % 8.9 Vol %
Vapour pressure at 20 °C:	6 hPa
Density at 20 °C: Relative density Vapour density Evaporation rate	0.906 g/cm³ Not determined. Not determined. Not determined.
Solubility in / Miscibility with water at 20 °C:	0.24 g/l
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic at 20°C: Kinematic: Other information	0.73 mPas Not determined. No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity

· LD/LC5	0 values rel	evant for classification:
Oral	LD50	5 000 mg/kg (rat)

(Contd. on page 6)

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

(Contd. of page 5)

Inhalative LC50/4 h 24 mg/l (rat)

- Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

14 Trans	port inj	tormat	ion
----------	----------	--------	-----

- · UN-Number
- · ADR, IMDG, IATA

UN2055

- · UN proper shipping name
- \cdot ADR
- · IMDG, IATA

2055 STYRENE MONOMER, STABILIZED STYRENE MONOMER, STABILIZED

- · Transport hazard class(es)
- · ADR, IMDG, IATA



- · Class 3 Flammable liquids.
- · Label .

(Contd. on page 7)

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

	(Contd. of pa	
Packing group		
ADR, IMDG, IATA	III	
Environmental hazards:	Not applicable.	
Special precautions for user	Warning: Flammable liquids.	
Hazard identification number (Kemler code):	39	
EMS Number:	3-07	
Stowage Category	C	
Stowage Code	SW1 Protected from sources of heat.	
Transport in bulk according to Annex II of Mar	pol	
and the IBC Code	Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
Tunnel restriction code	D/E	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
· · ·	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
UN "Model Regulation":	UN 2055 STYRENE MONOMER, STABILIZED, 3, III	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · GHS label elements

The substance is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms





GHS02

- · Signal word Warning
- · Hazard statements

Flammable liquid and vapour.

May be harmful if swallowed.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting equipment.

Avoid breathing dust/fume/gas/mist/vapours/spray.

(Contd. on page 8)

Printing date 24.01.2021 Revision: 24.01.2021

Trade name: Styrene

(Contd. of page 7)

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department.
- · Contact: PME
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

 $Flam.\ Liq.\ 3:\ Flammable\ liquids-Category\ 3$

Acute Tox. 5: Acute toxicity - oral - Category 5

Acute Tox. 4: Acute toxicity - inhalation - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

ΑE